



FEATURES	
A	ALL-ALUMINUM CASE, SCREENED VENT AND DRAIN HOLES
B	4 MOUNTING HOLES, FURNISHED WITH 4 2-1/2" #10 SCREWS, ALTERNATE FASTENING THROUGH INSIDE OF CASE, SMALLER FLANGE AND NO HOLES
C	1-1/2" FLANGE FOR MOUNTING
D	ILLUMINATION (SEE WIRE DIAGRAM), BACK-LIT WITH WHITE 100,000 HR SIGN-GRADE LED'S (SPECIFY COLOR TEMPERATE AS NEEDED)
E	TEMPERED GLASS CRYSTAL PROTECTING THE DIAL AND HANDS
F	1- 18 / 4 CABLE TO CONNECT TO MASTER CLOCK CONTROLLER: 2 - 24V LED POWER, 2 - 24V IMPULSE FOR CLOCK MOVEMENT
G	TRANSLUCENT WHITE SIGN-GRADE, UV PROTECTED, POLYCARBONATE DIAL
H	FULLY-ENCLOSED, ALL-ALUMINUM CASE
I	ARCHITECTURAL GRADE POWDER COATING
J	STAINLESS STEEL FASTENERS THROUGHOUT

DIMENSIONS		24" CLOCK	30" CLOCK	36" CLOCK	42" CLOCK
BB	1 CASE DIAMETER	24"	30"	36"	42"
	2 FACE OPENING	21 1/2"	27"	33"	39"
	3 CASE DEPTH	7"	7"	7"	7"
ORDERING KEY		AA-BB-CC-DD (SHOWN): SF-30-STD. ROMAN/ROMAN SPADE*-BLACK)			
AA	MODEL NUMBER	SF			
BB	SIZE	SEE DIMENSIONS (30" SHOWN)			
CC	DIAL/HAND	SEE SEPARATE SELECTION PAGES*			
DD	COLOR	BLACK (DEFAULT), BRONZE, SILVER, GREY, SPEC.			

TITLE: CASE CLOCK, SEMI-FLUSH MOUNTED, 42" & SMALLER			
SCALE: N/A	DATE:	DRAWN:	CHECKED:
DRAWING NO:	REVISION:		

LUMICHRON.COM
11460 Dorsett Road, Maryland Heights, MO 63043
616-245-8888 SALES@LUMICHRON.COM