	E, G B UNICORRON	
FEATURES		NOTES: DEDUCT 2" F
А	FULLY ENCLOSED ALL-ALUMINUM CASE, SCREENED VENT ON BACK	ADD 3" TO C
В	1-1/2" FLANGE FOR MOUNTING, LIP OVER ROUGH OPENING	CASE TO FIT
С	8" OF CLOCK BODY THROUGH THE WALL	
D	CLOCK FASTENS WITH 8 INSIDE SCREWS TO JAMS	
E	ILLUMINATION (SEE WIRE DIAGRAM), BACK-LIT WITH WHITE 100,000 HR SIGN-GRADE LED'S (SPECIFY COLOR TEMPERATE AS NEEDED)	
F	TEMPERED GLASS CRYSTAL PROTECTING THE DIAL AND HANDS	
G	TRANSLUCENT WHITE SIGN-GRADE, UV PROTECTED, POLYCARBONATE DIAL	
н	ARCHITECTURAL GRADE POWDER COATING	
I	STAINLESS STEEL FASTENERS THROUGHOUT	
J	COMPLETE SERVICE ACCESS THROUGH REMOVABLE BACK AND BUTTERFLY DOORS	
к	J-BOX FOR 24V MOVEMENT CONTROL WIRE, CONNECT TO MASTER CLOCK CONTROLLER LENGTH TBD, MAX 400'	
L	J-BOX FOR ILLUMINATION, 120V, .7 AMP, CONTROL BY OWNER	
L		

TITLE:

SCALE:

